

# MELO LIFT MODEL MLT-844C

## SPECIFICATIONS

<b>MODEL</b>	<b>MLT-844C</b>		
<b>ENGINE</b>	Perkins I100 Series Turbo		
<b>HORSEPOWER</b>	99bhp		
<b>TRANSMISSION</b>	CLARK 3 SPEED POWER SHIFT TRANSMISSION		
<b>AXLE</b>	OUTBOARD PLANETARY DRIVE 45% LIMITED SLIP DIFFERENTIAL		
<b>BRAKE SYSTEM</b>	HYDRAULIC POWERED BRAKES ON 4 WHEELS WET DISC SYSTEM		
<b>PARKING BRAKE</b>	DIFFERENTIAL MOUNTED S.A.H.R. WET DISC		
<b>DRIVE SYSTEM</b>	4 WHEEL DRIVE		
<b>STEERING</b>	2 WHEEL, 4 WHEEL, CRAB		
<b>ELECTRICAL SYSTEM</b>	12 VOLT-NEGATIVE GROUND 4D1000 SERIES BATTERY		
<b>CAPACITY</b>	(AT 24" LOAD CENTER)	8000 lbs-14FT 5000 lbs-22FT 1500 lbs-30ft	
<b>MAST</b>	HEIGHT	<u>LOWERED</u>	134"
		<u>SHIPPING HEIGHT</u>	120"
	LIFTING HEIGHT		22ft
<b>DIMENSIONS</b>	OVERALL LENGTH (less forks)	156"	
	OVERALL HEIGHT TO TOP OF CANOPY	105.5"	
	OVERALL WIDTH	88"	
	GROUND CLEARANCE	18"	
	WHEEL BASE	88"	
	OUTSIDE TURNING RADIUS	144"	
<b>TRAVEL SPEED</b>		APPROX., 20mph	
<b>TIRES</b>		GOODYEAR (16.9 x 24) 10 PLY	
<b>VEHICLE WEIGHT</b>		APPROX., 15000lbs	



## STANDARD EQUIPMENT

- Perkins Turbo Engine
- Dry Type Air Filter
- Circulating Block Heater
- Clark 3 Speed Power Shift Transmission
- Automatically Activated S.A.H.R. parking Brake
- Clark Axles with a Wet Disc Brake System
- Hydraulic Powered Brakes with Accumulators
- 22ft - 4 stage Roller Mast with a Clear View Design
- Maintenance Free Mast Chain Pulley's
- 4ft Carriage
- 4ft Forks
- Frame Leveling
- Chrome Exhaust Pipe
- Hydraulic Oil Level Sight Brake Gauge-Circuit Breakers on Dash
- Goodyear Tires
- Lock Up Tool Box
- Complete Lighting System Containing Front Lights, Rear Lights, Flasher Lights & Reverse Lights
- Horn on Steering Wheel
- Back Up Alarm
- Safety Neutral Switch
- Glow Plug
- Heavy Duty Key Switch with Accumulators-Hour Meter
- Amp Meter
- Engine Oil Pressure Gauge
- Water Temperature Gauge
- Fuel Level Gauge
- Transmission Oil Temperature Gauge
- Warning Lights For Oil Pressure, Battery & Parking -Brake
- Circuit Breakers on Dash
- Level Indicator
- Hydraulically Operated Engine Cover

## OPTIONAL EQUIPMENT

5ft. Carriage, 5ft. Forks, Compressor with Air Gauge, All Steel Cab with Safety Glass, Battery Kill Switch, Tire Sealant, Matched Set Padlocks, Fork Positioner.

## FORKLIFT MEETS ANSI B56.6 STANDARDS

The information contained herein is general in nature and is not intended for specific application purposes.

**DEMELO'S CONSTRUCTION EQUIPMENT LTD.** Reserves the right to make changes in specification shown, herein & improvements, or discontinue manufacture at any time without notice or obligation.

**DEALER:**



## MELO LIFT INC.

576 Fenmar Drive, Toronto, ON M9L 2S4

TEL: 416-741-9095 • FAX: (416) 740-5530

Website: www.melolift.com • E-mail: info@melolift.com